


DYWANOWE BASIC CARPET TILES BASIC

AVAILABLE SHAPES & SIZES

* Minimum order required.
For more details please contact to Boccho office.

BOCCHO® reserves the right to improve the specification of all products without prior notification.
Orders are subject to BOCCHO® terms and conditions of sale.

size 60x60, 100x100, 25x100, 50x100, 100x200 - minimum order applies - please check



Nazwa / Product name	Cena / Price EUR/m ² loco Konin	Rozmiar płytki / Tile size (standard)	Ilość m ² w kartonie / sqrm in box	Min. zamówienie / MOQ (min order)	Rodzaj ISO2424 / Construction	Runo (skład) ISO2424 / ISO2424 Pile Yarn Description	Waga okrywy efektywnej mm ISO2424.5.17 Pile Yarn Weight	Waga całkowita g/m2 ISO8543 / Total Weight	Grubość okrywy efektywnej mm ISO2424.5.17 / Pile Height
WOLIN 420 (Flat)	19,99	50 cm x 50 cm	5	5 m ²	Loop pile	PA SD	420	3 490	2,0
WOLIN 520	19,80	50 cm x 50 cm	5	5 m ²	Loop pile	Premium PA SD	520	4 300	3,5
WOLIN 620	22,41	50 cm x 50 cm	5	500 m ²	Loop pile	Premium PA SD	620	4 420	3,5
WOLIN 680	24,11	50 cm x 50 cm	5	500 m ²	Loop pile	Premium PA SD	680	4 480	3,5
URBAN	26,71	50 cm x 50 cm	5	5 m ²	Loop pile	Premium PA SD	750	4 540	3,4
BRICK	28,64	50 cm x 50 cm	5	5 m ²	Cut & Loop pile	PA 6.6 Antron Lumena	780	4 620	3,0
7EVEN	27,87	50 cm x 50 cm	5	5 m ²	Loop pile	PA 6.6 Antron Lumena	650	4 140	2,5

Wysokość całkowita mm / Total thickness	Gauge	Stitch	Gęstość taftowania m ² ISO1763 / Tufts per m ²	Podłoże ISO2424 / Backing	Trudnopalność EN13501 Em13501 / Flammability	Ilość kolorów / Number of cols	Rodzaj barwienia / Dye Method	Ogrzewanie podłogowe / Heating floors	Antystatyka kV ISO6356/ Body Voltage Test	Klasa użytkowa / Wear rating	Odporność na płowienie / Light resistance	Gwarancja / Warranty
5,0	1/12"	10	172 050	B-back	C _{ff} s1	15	SD	+	ISO 6356:2000 <2kV	33	+	15 years
7,0	1/10"	12	187 150	B-back	C _{ff} s1	15	SD	+	ISO 6356:2000 <2kV	33	+	10 years
7,0	1/10"	13	202 910	B-back	C _{ff} s1	15	SD	+	ISO 6356:2000 <2kV	33	+	10 years
7,0	1/10"	12	189 120	B-back	C _{ff} s1	15	SD	+	ISO 6356:2000 <2kV	33	+	10 years
7,0	1/10"	6,2	96 100	B-back	B _{ff} s1	8	SD	+	ISO 6356:2000 <2kV	33	+	10 years
6,5	1/12"	12	226 560	B-back	B _{ff} s1	8	SD	+	ISO 6356:2000 <2kV	33	+	10 years
6,0	1/12"	11,7	217 620	B-back	B _{ff} s1	12	SD	+	ISO 6356:2000 <2kV	33	+	10 years